



## HIGH GLOSS AROMATIC FREE PU TOPCOAT RANGE

EXCELLENT BODY

VERY GOOD LEVELLING

EXTREMELY FAST DRYING

218-9005/95    White  
218-0005/95    Clear

**OECE**

**COLOR:** WHITE and CLEAR  
**PRODUCT SECTOR:** INTERIOR FURNISHING  
**APPLICATION SYSTEMS:** SPRAY, AUTOMATIC / ROBOT MACHINE  
**SUBSTRATE:** MDF

These aromatic free PU topcoats can be applied by automatic spraying machines or by traditional hand method.


Thanks to the possibility to apply thick layers, **218-9005/95** and **218-0005/95** are suitable to work directly on melamine paper previously sanded with sand papers with finer grit, down to 600. When properly sanded, the first layer of **218-XX05/95** can be applied with an amount of 180-250 gr/sqm.

They are characterized by a smooth and slick finish, and can be tinted with PU pastes for tinting system.

**218-9005/95** is stackable after 4-6 hours after forced drying at 35-40°C.

**218-0005/95** is stackable after 5-7 hours after forced drying at 35-40°C.

Thanks to the absence of the aromatic chemicals the products have a better labelling, showing no more the pictogram of long-term toxicity.



COATING SYSTEM	PRODUCTS	
Aromatic free high gloss 2K PU topcoat	218-XX05/95	+ 812-20 70-100%
		+ 922-03 30-70%

TECHNICAL PROPERTIES	ADVANTAGES
QUICK DRYING	High gloss coating system with excellent body
EXCELLENT ADHESION	Mechanical shock resistant
GOOD CHEMICAL RESISTANCE	Resistant to cold liquids
OUTSTANDING HARD SURFACE	Scratch resistant

For the definition of a specific coating system, please contact our Technical Service.



strong **beautiful** surfaces

OECE is a brand of  
The Sherwin-Williams Company

**Sherwin-Williams Italy S.r.l. - Export Department**

Via del Fiffò 12

40065 Pianoro (BO) - Italy

Ph.: +39 051 770511 - Fax: +39 051 770528

export@oece.it

Technical Service: ph. +39 051 770770 - fax +39 051 770521

technicalservice@sherwin.com

www.oece.it

04/2020  
Z09A19.1