



ACRYLIC WHITE PIGMENTED BASECOAT FOR OPEN PORE

SUPERB HIGH BUILD

SHARP PORE DEFINITION

PERFECT COVERAGE

430-9005/5



COLOR: WHITE
PRODUCT SECTOR: INTERIOR FURNISHING
APPLICATION SYSTEMS: SPRAY, CURTAIN COATER
SUBSTRATES: FURNITURE, PANELS, DOORS

430-9005/5 is the acrylic white pigmented basecoat for open pore characterized by superb high build and sharp pore definition.


This acrylic pigmented basecoat has been specially developed to produce a clear pore definition while maintaining high build and even coverage properties.

The exceptional pore wetting properties of **430-9005/5** ensure a completely sealed surface, even on difficult to coat substrates such as oak.

Designed for furniture, panels and doors, **430-9005/5** can also be tinted and used as basecoat of a decapé coating system.

The high surface quality and even coverage achieved with **430-9005/5** often results in reduced application rates.

A very generous pot-life (12-15 hours) also simplifies production planning.



CHARACTERISTICS	ADVANTAGES
SUPERB SUBSTRATE WETTING	High build and sharp pore definition combined
	Perfect coverage even on oak
TINTABLE AND OVERCOATABLE	Can be used in a decapé coating system
LONG POT-LIFE	Simple production control

PRODUCT SPECIFICATIONS	
APPLICATION	Air spray, airmix, robot, curtain coater
DRYING / STACKING	4 hours at 20°C or 1 hour at 60°C for typical 160 g/m ² application
DILUTION	25-40% with 922-03 , as required
HARDENER	25% vol. 813-01

07/2019
Z02A66.UK



strong **beautiful** surfaces

OECE is a brand of
The Sherwin-Williams Company

Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffò 12

40065 Pianoro (BO) - Italy

Ph.: +39 051 770511 - Fax: +39 051 770528

export@oece.it

Technical Service: ph. +39 051 770770 - fax +39 051 770521

technicalservice@sherwin.com

www.oece.it