



5 GLOSS CLEAR ACRYLIC POLYURETHANE TOPCOAT

SMOOTH TO THE TOUCH

OPEN PORE EFFECT

EXCEPTIONAL RESISTANCE

410-0024/05



COLOR: CLEAR
PRODUCT SECTOR: INTERIOR FURNISHING
APPLICATION SYSTEMS: SPRAY, CURTAIN COATER
SUBSTRATES: LIGHT AND DARK TIMBERS



410-0024/05 is the 2K clear 5 gloss acrylic polyurethane topcoat developed to bring out a warm and matt appeal, both on light and dark timbers.

As a result to our internal testing, thanks to its characteristics, the product is in compliance to UNI EN 12721 and 12722, as well as to CEN/TS 16209, hence it is the perfect solution for interior furniture that require particular attention in terms of resistance to heat, abrasion and scratches.

Not only **410-0024/05** protects the wood, it also highlights its grain, for an outstanding natural look in every spot of the house.

The aesthetic is enhanced by the smoothness to the touch, making it ideal for an even more appealing design.

Non yellowing, fast drying, **410-0024/05** is for use on acrylic basecoats, as well as overcoatable with itself, meaning it can be used as a self-sealer.



CHARACTERISTICS	ADVANTAGES
EXCELLENT CHEMICAL RESISTANCE	Good resistance to alcohol, acetone, ammonia
	Ideal for kitchen cabinets, bathrooms
DEEP MATT	Perfect to brighten open pores
	Smooth to the touch

PRODUCT SPECIFICATIONS	
APPLICATION	Spray, curtain coater
DRYING 20°C for typical 80-120 g/m ² application	Dust Free: 10-15 mins
	Touch Dry: 20-30 mins
HARDENER	20% weight 813-30
STACKING	6-8 hours



strong **beautiful** surfaces

OECE is a brand of
The Sherwin-Williams Company

Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffio 12

40065 Pianoro (BO) - Italy

Ph.: +39 051 770511 - Fax: +39 051 770528

export@oece.it

Technical Service: ph. +39 051 770770 - fax +39 051 770521

technicalservice@sherwin.com

www.oece.it