



NEW CONVERTER ACRYLIC PU MATT

STABLE OVER TIME, LIGHT FAST

SYSTEM FULLY COMPATIBLE WITH PU
PASTES

VERSATILE

410-XX98XX

Matt



SECTOR OF USE:
APPLICATION:

FLAT PARTS, DOORS, FURNITURE
MANUAL SPRAY, ROBOT

Two-component acrylic converter OECE **410-XX98XX** for the production of custom lacquered topcoats, dedicated to the interior design sector, doors, furniture, kitchens, where the demand for acrylic solutions increases above all driven by the needs of design. Born above all to offer an effective acrylic tintometric solution to all users of automatic dispensers.

Available in white and transparent in 5-10-25 gloss opacities, it can be applied by cup and airless spray, by robot. **410-XX98XX** is the non-yellowing solution, stable over time, to reproduce all colours. Acrylic system fully compatible with PU pastes, therefore with the tinting system, to achieve a more versatile and competitive tinting range, able to satisfy every need. **410-XX98XX** is an acrylic converter which perfects the reliability of the 241-XXXX tintometric system by improving aesthetic and performance results such as distension, homogeneity of the surfacing of the opaque on the surface, pore cutting.

Good flow, coverage and softness. High pot life.



TECHNICAL FEATURES			
SECTOR OF USE	Flat parts, doors, furniture.		
APPLICATION	Manual spray, robot.		
CATALYSIS AND DILUTION			By weight (kg)
	410-XX98XX		100
	813-01		20
	922-12		30-40
DRYING		20°C	50°C
	dust free	30 minn	
	touch free	1 h	
	stackable	5 h	80-90 mins

07/2023
Z09A29UK



strong **beautiful** surfaces

OECE is a brand of
The Sherwin-Williams Company

Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffio 12

40065 Pianoro (BO) - Italy

Ph.: +39 051 770511 - Fax: +39 051 770528

export@oece.it

Technical Service: tel. +39 051 770770 - fax +39 051 770521

servizioclienti@sherwin.com

www.oece.it