



SUPERB MECHANICAL &
CHEMICAL RESISTANCE

EFFORTLESSLY REPAIRABLE &
CLEANABLE SURFACE

ANTI-FINGERPRINT

SILKY ARMOR HP
TWO-COMPONENT 2K POLYURETHANE
ULTRA LOW GLOSS TOPCOAT WITH
SMOOTH & SATIN EFFECT

410-0003 / 03

Clear

410-9003 / 03

White



COLOR: CLEAR, WHITE
SECTOR OF USE: FURNITURE, INTERIOR FURNISHINGS AND KITCHENS
APPLICATION SYSTEMS: SPRAY
SUPPORTS: MDF AND MELAMINE PAPER

Silky Armor HP, the innovative solvent-borne ultra matt High Performances finishing, is the ideal choice for customers seeking high chemical performance, mechanical resistance, and excellent hiding power. With very good self-reparability performance, it offers a long-lasting, high aesthetic and functional quality. The surface finish durability is guaranteed by its unique properties, allowing effortless cleaning and the removal of superficial scratches.

2k Special Polyurethan formulation with high chemical performances and physical resistances. Alternative to latest technologies as excimer and plastic-foils, with the advantage of not directional spray application, good for every surface, even tridimensional. Without any need of additional investments or machinery. It can be applied on any kind of solvent basecoat or directly on sanded melamine paper. Very good adhesion and hiding power in a single layer (120 g/m², spray).

Fully compatible with our tinting- system, ensuring unlimited colour matching and customization using limited quantity of standard solvent borne pastes (< 10%).



Substrate preparation.

The substrates can be prepared with PU primers of the desired colour, for 410-0003/03. Use standard PU/PE primers for 410-9003/03. The product can be pigmented with 241-XX pastes, at a percentage between 5-10% by weight.

CARATTERISTICHE TECNICHE						
PRODUCT	GLOSS	CODE	TYPE	COVERAGE	DRYING CONDITIONS	DRYING TIME
SILKY ARMOR HP	2 +/- 1	410-0003/03	Clear	100-150 g/m ²	100 g/m ² Room temperature 20°C	Touch dry 2-4h
						Through dry 24h
		410-9003/03	White	120-170 g/m ²	120 g/m ² Room temperature 20°C	Touch dry 3-4h
						Through dry 36h

Please refer to official products TDS (Technical Data sheets) for additional information and application suggestions.

07/2023
Z09A50.LIK



strong beautiful surfaces

OECE is a brand of
The Sherwin-Williams Company

Sherwin-Williams Italy S.r.l.

Via del Fiffò 12

40065 Pianoro (BO) - Italia

Tel.: +39 051 770511 - Fax: +39 051 777437

info@oece.it

Servizio Clienti: tel. +39 051 770770 - fax +39 051 770521

servizioclienti@sherwin.com

www.oece.it